

Filtro Tasche Sintetico



ARTICOLO	COMPOSIZIONE	DIMENSIONE (mm)	TASCHE	SUPERFICIE FILTRANTE (m ²)	PORTATA D'ARIA (m ³ /h)	PERDITA DI CARICO INIZIALE (Pa)	CLASSE FILTRAZIONE EN 779:2012	CLASSE FILTRAZIONE ISO 16890
G3AB25319	poliestere	287 x 592 x 200	3	0,67	1100	60	G3	ISO Coarse 60%
G3AB25336	poliestere	287 x 592 x 360	3	1,28	2080	60	G3	ISO Coarse 60%
G3AB25350	poliestere	287 x 592 x 500	3	1,78	2880	60	G3	ISO Coarse 60%
G3AB25360	poliestere	287 x 592 x 620	3	2,20	3570	60	G3	ISO Coarse 60%
G3AB25419	poliestere	492 x 592 x 200	4	0,90	1460	60	G3	ISO Coarse 60%
G3AB25436	poliestere	492 x 592 x 360	4	1,70	2770	60	G3	ISO Coarse 60%
G3AB25450	poliestere	492 x 592 x 500	4	2,37	3840	60	G3	ISO Coarse 60%
G3AB25460	poliestere	492 x 592 x 620	4	2,94	4760	60	G3	ISO Coarse 60%
G3AB25519	poliestere	592 x 592 x 200	6	1,35	2190	60	G3	ISO Coarse 60%
G3AB25536	poliestere	592 x 592 x 360	6	2,56	4150	60	G3	ISO Coarse 60%
G3AB25550	poliestere	592 x 592 x 500	6	3,55	5760	60	G3	ISO Coarse 60%
G3AB25560	poliestere	592 x 592 x 620	6	4,40	7140	60	G3	ISO Coarse 60%
ARTICOLO	COMPOSIZIONE	DIMENSIONE (mm)	TASCHE	SUPERFICIE FILTRANTE (m ²)	PORTATA D'ARIA (m ³ /h)	PERDITA DI CARICO INIZIALE (Pa)	CLASSE FILTRAZIONE EN 779:2012	CLASSE FILTRAZIONE ISO 16890
G4AB35319	poliestere	287 x 592 x 200	3	0,67	1100	70	G4	ISO Coarse 70%
G4AB35336	poliestere	287 x 592 x 360	3	1,28	2080	70	G4	ISO Coarse 70%
G4AB35350	poliestere	287 x 592 x 500	3	1,78	2880	70	G4	ISO Coarse 70%
G4AB35360	poliestere	287 x 592 x 620	3	2,20	3570	70	G4	ISO Coarse 70%
G4AB35419	poliestere	492 x 592 x 200	4	0,90	1460	70	G4	ISO Coarse 70%
G4AB35436	poliestere	492 x 592 x 360	4	1,70	2770	70	G4	ISO Coarse 70%
G4AB35450	poliestere	492 x 592 x 500	4	2,37	3840	70	G4	ISO Coarse 70%
G4AB35460	poliestere	492 x 592 x 620	4	2,94	4760	70	G4	ISO Coarse 70%
G4AB35519	poliestere	592 x 592 x 200	6	1,35	2190	60	G4	ISO Coarse 70%
G4AB35536	poliestere	592 x 592 x 360	6	2,56	4150	60	G4	ISO Coarse 70%
G4AB35550	poliestere	592 x 592 x 500	6	3,55	5760	60	G4	ISO Coarse 70%
G4AB35560	poliestere	592 x 592 x 620	6	4,40	7140	60	G4	ISO Coarse 70%