Enclosed Speakers

HTX 8 M-CL-W/C

200 (8) mm (in.) | 288 (11.34) mm (in.) | Led Clamp Tower | 200 W | 4 Ohm



Are you ready to enjoy your favorite track at high output level during your daily water ski session? Hertz Marine Towers will make your sport and leisure outings unforgettable, thanks to impressive audio performance and cool color lighting. The solid 316-Stainless steel clamp mounting is ideal for Round or Square profile pipe applications where sound needs to be easily oriented and quickly released. This is possible thanks to Q-OS² (Quick Orientation & Release for Sound & Safety) patent pending technology. “ **Adjustable logo**” allows for several tower positioning without affecting the correct Hertz logo orientation. Front and rear logo can be oriented within 64 steps.

TECHNICAL SPECS

Component	LED CLAMP TOWER
Size	200 (8) mm (in.)
Power Handling - Continuous	100 W
Power Handling - Peak	200 W
Impedance	4 Ohm
Depth	288 (11.34) mm (in.)
Tweeter diaphragm	36 (1.4) mm (in.)
Woofer Voice Coil Ø	32 (1.26) mm (in.)
Tweeter Voice Coil Ø	20 (0.8) mm (in.)
Frequency Response	45 ÷ 25k Hz
Woofer Magnet size D x d x h	90 x 40 x 20 (3.54 x 1.57 x 0.79) mm (in.)
Tweeter Magnet size D x h	19,7 x 3 (0.78 x 0.12) mm (in.)
Weight of one speaker	5,4 (11.9) kg (lb.)
Woofer Magnet	High density flux ferrite
Tweeter Magnet	Neodymium
Cone	Polypropylene with UV inhibitors
Dome	PEI
Xmech	±8,5 (0.33) mm (in.)

ELECTRIC-ACOUSTIC SPECS

D	174 mm
Re	3,4 Ohm
Fs	51 Hz

All the specifications subject to change without notice_20.A

Technology Art & Sound
Manufactured by elettromedia Italy

Elettromedia
62018 Potenza Picena (MC) Italy
T +39 0733 870 870 - F +39 0733 870 880
elettromedia.com

HERTZ

Le	0,46 mH
Vas	26,1 l
Mms	30 g
Cms	0,33 mm/N
BL	6,33 T*m
Qts	0,78
Qes	0,82
Qms	14,7
Spl	91 dB

PHYSICAL SPECS

All the specifications subject to change without notice_20.A

Elettromedia
62018 Potenza Picena (MC) Italy
T +39 0733 870 870 - F +39 0733 870 880
elettromedia.com