In-Ceiling

HEX 6.5 IC-W

165 (6.5) mm (in.) | 87 (3.43) mm (in.) | In-ceiling Coax | 100 W | 6 Ohm



TECHNICAL SPECS

Component	IN-CEILING COAX
Size	165 (6.5) mm (in.)
Power Handling - Continuous	50 W
Power Handling - Peak	100 W
Impedance	6 Ohm
Depth	87 (3.43) mm (in.)
Tweeter diaphragm	24 (0.9) mm (in.)
Woofer Voice Coil Ø	25 (1) mm (in.)
Tweeter Voice Coil Ø	20 (0.8) mm (in.)
Frequency Response	50 ÷ 22k Hz
Woofer Magnet size D x d x h	75 x 32 x 15 (2.95 x 1.26 x 0.59) mm (in.)
Tweeter Magnet size D x h	19 x 3 (0.75 x 0.12) mm (in.)
Weight of one speaker	1.75 (3.86) kg (lb.)
Woofer Magnet	High density flux ferrite
Tweeter Magnet	Neodymium
Cone	Polypropylene with UV inhibitors
Dome	Tetolon
Xmech	?4,8 (0.19) mm (in.)

ELECTRIC-ACOUSTIC SPECS

D	125 mm
Re	5 Ohm
Fs	60 Hz
Le	0.32 mH
Vas	10.48 l
Mms	14.2 g
Cms	0.50 mm/N

All the specifications subject to change without notice_20.A

Elettromedia
62018 Potenza Picena (MC) Italy
T +39 0733 870 870 - F +39 0733 870 880
elettromedia.com

BL	5.3 T*m
Qts	0.81
Qes	0.98
Qms	4.8
Spl	88 dB

PHYSICAL SPECS

All the specifications subject to change without notice_20.A

Elettromedia
62018 Potenza Picena (MC) Italy
T +39 0733 870 870 - F +39 0733 870 880
elettromedia.com